SAFETY DATA SHEET					
	according to Regulation (EC) No 1907/2006 (REACH) as amended				
		Polyurethane Liquid Glue			
	on date 27th October 2020	-			
Revisi	on date 21st June 2022	Version 3.0			
		mixture and of the company/undertaking			
1.1.	Product identifier	Titebond Polyurethane Liquid Glue			
	Substance / mixture	mixture			
	UFI Delevent identified was a fithe substant	3QU2-2JXA-3308-TEQ2			
1.2.	Mixture's intended use Wood glue.	nce or mixture and uses advised against			
	Main intended use PC-ADH-6 Adhesives	s and sealants - woodworking and joinery (includes putty)			
	Mixture uses advised against				
	The product should not be used in ways o	ther then those referred in Section 1.			
1.3.	Details of the supplier of the safety d				
	Distributor				
	Name or trade name	IGM nástroje a stroje s.r.o.			
	Address	Ke Kopanině 560, Tuchoměřice, 252 67			
		Czech Republic			
	Identification number (CRN)	25114727			
	VAT Reg No	CZ25114727			
	Phone	+420 220 950 910			
	E-mail	prodej@igm.cz			
	Web address	igm.cz			
	Importer				
	Name or trade name	IGM nástroje a stroje s.r.o.			
	Address	Ke Kopanině 560, Tuchoměřice, 252 67			
		Czech Republic			
	Identification number (CRN)	25114727			
	VAT Reg No	CZ25114727			
	Phone	+420 220 950 910			
	E-mail	prodej@igm.cz			
	Web address	igm.cz			
	Manufacturer				
	Name or trade name	Franklin International			
	Address	2020 Bruck Street, Colombus OH, 43207			
		United States of America			
	Phone	(800) 877-4583			
	Supplier Name or trade name				
		Franklin International			
	Address	2020 Bruck Street, Colombus OH, 43207 United States of America			
	Phone				
	Competent person responsible for the	(800) 877-4583			
	Name	IGM nástroje a stroje s.r.o.			
	E-mail	prodej@igm.cz			
1.4.	Emergency telephone number	prodejæigni.cz			
	European emergency number: 112				

according to Regulation (EC) No 1907/2006 (REACH) as amended

Titebond Polyurethane Liquid Glue

Creation date Revision date

27th October 2020 21st June 2022

Version

3.0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 3, H331 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse effects on human health and the environment

Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. Suspected of causing cancer. Harmful if inhaled.

2.2. Label elements

Hazard pictogram



Signal word Danger

Hazardous substances

4,4'-methylenediphenyl diisocyanate Polymeric diphenylmethane diisocyanate, Polymeric MDI methylenediphenyl diisocyanate 2,4-dioxo-1,3-diazetidine-1,3-diylbis[p-phenylenemethylene-p-phenylene] diisocyanate

Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311	If experiencing respiratory symptoms: Call a doctor.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.
Supplemental information	
EUH204	Contains isocyanates. May produce an allergic reaction.



according to Regulation (EC) No 1907/2006 (REACH) as amended

Titebond Polyurethane Liquid Glue

Creation date Revision date 27th October 2020 21st June 2022

Version

3.0

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 615-005-00-9 CAS: 101-68-8 EC: 202-966-0	4,4'-methylenediphenyl diisocyanate	≤25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373 Specific concentration limit: Eye Irrit. 2, H319: $C \ge 5$ % Resp. Sens. 1, H334: $C \ge 0,1$ % STOT SE 3, H335: $C \ge 5$ % Skin Irrit. 2, H315: $C \ge 5$ %	1, 2, 3
CAS: 9016-87-9 EC: 618-498-9	Polymeric diphenylmethane diisocyanate, Polymeric MDI	≤10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373 EUH204 Specific concentration limit: Eye Irrit. 2, H319: $C \ge 5 \%$ Skin Irrit. 2, H315: $C \ge 5 \%$ Resp. Sens. 1, H334: $C \ge 0,1 \%$ STOT SE 3, H335: $C \ge 5 \%$	
Index: 615-005-00-9 CAS: 26447-40-5 EC: 247-714-0	methylenediphenyl diisocyanate	≤3	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373 Specific concentration limit: STOT SE 3, H335: $C \ge 5$ % Eye Irrit. 2, H319: $C \ge 5$ % Skin Irrit. 2, H315: $C \ge 5$ % Resp. Sens. 1, H334: $C \ge 0,1$ %	1, 2, 3



according to Regulation (EC) No 1907/2006 (REACH) as amended

Titebond Polyurethane Liquid Glue

Creation date Revision date	27th October 2020 21st June 2022	Version	3.0	
	zist Julie 2022	Version	5.0	
		Content in	Classification according to	

Identification numbers	Substance nameContent in % weightClassification according to Regulation (EC) No 1272/2008		Classification according to Regulation (EC) No 1272/2008	Note
CAS: 17589-24-1 EC: 241-559-2	2,4-dioxo-1,3-diazetidine-1,3-diylbis[p- phenylenemethylene-p-phenylene] diisocyanate	≤0.3	Acute Tox. 4, H302+H332 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 (ingestion, inhalation) STOT SE 1, H370 (the respiratory system) (inhalation) STOT RE 1, H372 (respiratory tract (inhalation), lungs (inhalation)) (inhalation)	

Notes

- 1 Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- 2 Note 2: The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.
- 3 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Provide medical treatment. For persons with no symptoms, call the Toxicological Information Centre to decide about the need of medical treatment; provide information about the substances or composition of the product from the original packaging or the Safety Data Sheet of the product.

Most important symptoms and effects, both acute and delayed

If inhaled

4.2.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. **If on skin**

May cause an allergic skin reaction.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

according to Regulation (EC) No 1907/2006 (REACH) as amended

Titebond Polyurethane Liquid Glue

Creation date27th October 2020Revision date21st June 2022Version3.0

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in concentrations exceeding the occupational exposure limits. Do not inhale aerosols. Prevent contact with skin and eyes. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Wash hands and exposed parts of the body thoroughly after handling. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Keep container tightly closed.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

according to Regulation (EC) No 1907/2006 (REACH) as amended

Titebond Polyurethane Liquid Glue

Creation date	27th October 2020		
Revision date	21st June 2022	Version	3.0

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment. In case of inadequate ventilation wear respiratory protection.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1.	Information on basic physical and chemical properties	

Physical state	liquid
Colour	data not available
Odour	data not available
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	93.3 °C
Auto-ignition temperature	data not available
Decomposition temperature	data not available
рН	data not available
Kinematic viscosity	data not available
Solubility in water	data not available
Solubility in fats	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	data not available
Other information	
Evaporation rate	data not available

SECTION 10: Stability and reactivity

10.1. Reactivity

9.2.

not available

10.2. Chemical stability The product is stable under normal conditions.
10.3. Possibility of hazardous reactions

Unknown.

		CAEETV	DATA SHEET		
		SAFEIT	DATA SHEET		
		according to Regulation (EC	C) No 1907/2006 (REACH)	as amended	
		Titebond Poly	urethane Liquid	Glue	
Creatio	on date	27th October 2020	•		
Revisio	on date	21st June 2022	Version	3.0	
10.4.	Conditions to av	oid			
	The product is sta against frost.	ble and no degradation occurs	under normal use. Protec	t against flames, sparks,	overheating and
10.5.	-	aterials			
	Protect against str	ong acids, bases and oxidizing	agents.		
10.6.	Hazardous deco	mposition products			
	Not developed und high temperature	der normal uses. Dangerous oເ and in fire.	utcomes such as carbon me	pnoxide and carbon dioxid	de are formed a
	inhalation poisonir the mixture. Acute toxicity Harmful if inhaled. Skin corrosion/i Causes skin irritat Serious eye dam Causes serious eye Respiratory or sl May cause allergy Germ cell mutag Based on available Carcinogenicity Suspected of caus	rritation ion. age/irritation e irritation. kin sensitisation or asthma symptoms or breath enicity e data the classification criteria ing cancer.	ncentration and exposure	time. No toxicological dat	a is available fo
	Reproductive to	-			
	Based on available	e data the classification criteria	are not met.		

Toxicity for specific target organ - single exposure

May cause respiratory irritation.

Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

not available

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

2,4-dioxo-1,3-diazetidine-1,3-diylbis[p-phenylenemethylene-p-phenylene] diisocyanate

Parameter	Value	Exposure time	Species	Environment
	1000 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	
	1640 mg/l	72 hour	Algae (Selenastrum capricornutum)	

12.2. Persistence and degradability

Data not available.

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment



according to Regulation (EC) No 1907/2006 (REACH) as amended

Titebond Polyurethane Liquid Glue

Creation	date
Revision	date

27th October 2020 21st June 2022

Version

3.0

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

- **12.6.** Endocrine disrupting properties
- not available
- 12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

- 14.1. UN number or ID number
 - not subject to transport regulations
- 14.2. UN proper shipping name not relevant
- 14.3. Transport hazard class(es) not relevant
- **14.4.** Packing group not relevant
- 14.5. Environmental hazards not relevant
- **14.6.** Special precautions for user Reference in the Sections 4 to 8.
- **14.7.** Maritime transport in bulk according to IMO instruments not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

4,4'-methylenediphenyl diisocyanate

Restriction	Conditions of restriction
74	 Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless: (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture

IGM

according to Regulation (EC) No 1907/2006 (REACH) as amended

Titebond Polyurethane Liquid Glue

Creation date Revision date 27th October 2020 21st June 2022

Version

3.0

. ,	ediphenyl diisocyanate
Restriction	Conditions of restriction
	 (s). 2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless: (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or
	 (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use". 3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks. 4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national
	 occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum: (a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s). (b) the training elements in points (a) and (b) of paragraph 5 for the following uses: handling open mixtures at ambient temperature (including foam tunnels);
	 — spraying in a ventilated booth; — application by roller; — application by brush;
	 application by dipping and pouring; mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore; cleaning and waste;
	 any other uses with similar exposure through the dermal and/or inhalation route; (c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses: handling incompletely cured articles (e.g. freshly cured, still warm); foundry applications;
	 maintenance and repair that needs access to equipment; open handling of warm or hot formulations (> 45 °C); spraying in open air, with limited or only natural ventilation (includes large industry working halls)
	 and spraying with high energy (e.g. foams, elastomers); and any other uses with similar exposure through the dermal and/or inhalation route. Training elements: (a) general training, including on-line training, on:
	 chemistry of diisocyanates; toxicity hazards (including acute toxicity); exposure to diisocyanates;
	 occupational exposure limit values; how sensitisation can develop; odour as indication of hazard;
	 importance of volatility for risk; viscosity, temperature, and molecular weight of diisocyanates; personal hygiene;
	 personal protective equipment needed, including practical instructions for its correct use and its limitations; risk of dermal contact and inhalation exposure;
	 risk in relation to application process used; skin and inhalation protection scheme;
	 ventilation; cleaning, leakages, maintenance; discarding empty packaging;
	 protection of bystanders; identification of critical handling stages; specific national code systems (if applicable);
	 behaviour-based safety; certification or documented proof that training has been successfully completed (b) intermediate level training, including on-line training, on: additional behaviour-based aspects;

according to Regulation (EC) No 1907/2006 (REACH) as amended

Titebond Polyurethane Liquid Glue

Creation date Revision date 27th October 2020 21st June 2022

Version

3.0

4,4'-methylenediphenyl diisocyanate

Restriction	Conditions of restriction
	— maintenance;
	 management of change;
	 evaluation of existing safety instructions;
	 risk in relation to application process used;
	 certification or documented proof that training has been successfully completed
	(c) advanced training, including on-line training, on:
	 any additional certification needed for the specific uses covered;
	 spraying outside a spraying booth;
	 open handling of hot or warm formulations (> 45 °C);
	 certification or documented proof that training has been successfully completed
	6. The training shall comply with the provisions set by the Member State in which the industrial or
	professional user(s) operate. Member States may implement or continue to apply their own national
	requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements
	set out in paragraphs 4 and 5 are met.
	7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the
	Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into
	consideration the specificity of the products supplied, including composition, packaging, and design.
	8. The employer or self-employed shall document the successful completion of the training referred
	to in paragraphs 4 and 5. The training shall be renewed at least every five years.
	9. Member States shall include in their reports pursuant to Article 117(1) the following information:
	(a) any established training requirements and other risk management measures related to the
	industrial and professional uses of diisocyanates foreseen in national law;
	(b)the number of cases of reported and recognised occupational asthma and occupational respiratory
	and dermal diseases in relation to diisocyanates;
	(c) national exposure limits for diisocyanates, if there are any;
	(d) information about enforcement activities related to this restriction.
	10. This restriction shall apply without prejudice to other Union legislation on the protection of safety
	and health of workers at the workplace.

4,4'-methylenediphenyl diisocyanate, methylenediphenyl diisocyanate

Restriction	Conditions of restriction
56	 Shall not be placed on the market after 27 December 2010, as a constituent of mixtures in concentrations equal to or greater than 0,1 % by weight of MDI for supply to the general public, unless suppliers shall ensure before the placing on the market that the packaging: (a) contains protective gloves which comply with the requirements of Council Directive 89/686/EEC (********); (b) is marked visibly, legibly and indelibly as follows, and without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures: " – Persons already sensitised to diisocyanates may develop allergic reactions when using this product. – Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. – This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used."
	2. By way of derogation, paragraph 1(a) shall not apply to hot melt adhesives.

not available

15.2.

SECTION 16: Other infor	mation
A list of standard	risk phrases used in the safety data sheet
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.



ICM

according to Regulation (EC) No 1907/2006 (REACH) as amended

Titebond Polyurethane Liquid Glue

Creation date	27th October 2020			
Revision date	21st June 2022	Version	3.0	
H335	May cause respire	atory irritation.		
H351	Suspected of cau			
H351	-	Suspected of causing cancer if swallowed or if inhaled.		
H370	Causes damage t	Causes damage to the respiratory system if inhaled.		
H372		uses damage to the respiratory tract (inhalation), lungs (by inhalation) through longed or repeated exposure if inhaled.		
H373		•	blonged or repeated exposure.	
H302+H332	Harmful if swallow			
	for safe handling used in the safe			
P101	-	-	t container or label at hand.	
P102	Keep out of reach			
P271	-	s or in a well-ventilated	area.	
P280	Wear protective of	jloves.		
P304+P340	IF INHALED: Rem	nove person to fresh air	and keep comfortable for breathing.	
P342+P311		spiratory symptoms: Ca		
P405	Store locked up.			
P501		nts/container to by hand or by returning to the su	ing over to the person authorized to upplier.	
A list of add	ditional standard phrases used in	the safety data sheet		
EUH204	Contains isocyana	ates. May produce an all	ergic reaction.	
Other impo	rtant information about human h	ealth protection		
			rer/importer - used for purposes other that	
as per the S	ection 1. The user is responsible for a	dherence to all related	health protection regulations.	
	eviations and acronyms used in t			
ADR	European agreem road	ent concerning the inte	rnational carriage of dangerous goods by	
BCF	Bioconcentration	Factor		
CAS	Chemical Abstrac			
CLP	Regulation (EC) N substance and m		cation, labelling and packaging of	
EINECS	European Invento	ory of Existing Commerc	ial Chemical Substances	
EmS	Emergency plan			
ES	Identification cod	e for each substance list	ed in EINECS	
EU	European Union			
EuPCS	European Product	t Categorisation System		
IATA	International Air	Transport Association		
IBC			And Equipment of Ships Carrying	
	Dangerous Chem			
ICAO		International Civil Aviation Organization		
IMDG		International Maritime Dangerous Goods		
INCI		nenclature of Cosmetic I	-	
ISO	-	national Organization for Standardization		
IUPAC		on of Pure and Applied C	nemistry	
log Kow	Octanol-water pa		on of Dollution from China	
MARPOL			on of Pollution from Ships	
OEL PBT		cupational Exposure Limits rsistent, Bioaccumulative and Toxic		
ppm REACH	Parts per million Registration Eva	luation Authorization ar	d Restriction of Chemicals	
RID UN	-		ubstance or article taken from the UN	
UVCB	-	of unknown or variable composition, complex reaction products or		
VOC	Volatile organic c			
vPvB	-	nc compounds nt and very Bioaccumulative		

according to Regulation (EC) No 1907/2006 (REACH) as amended

Titebond Polyurethane Liquid Glue

Creation date	27th October 2020			
Revision date	21st June 2022	Version	3.0	

Acute Tox.	Acute toxicity
Carc.	Carcinogenicity
Eye Irrit.	Eye irritation
Resp. Sens.	Respiratory sensitization
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 3.0 replaces the SDS version from 10 February 2021. Changes were made in sections 2 and 16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

674